

CLAIMS:

- A method of fabricating a self-assembled monolayer of a substance on a substrate comprising depositing the substance on the substrate using compressed carbon dioxide as the solvent medium for the substance.
- A method as claimed in claim 1, wherein the pressure and/or temperature of the 2. compressed carbon dioxide is/are selectively controlled so as to enhance the density of the self-assembled monolayer on the substrate.
- A method as claimed in claim 1 or 2 comprising the use of a co-solvent in 3. combination with the compressed carbon dioxide.
- A method as claimed in claim 3, wherein the co-solvent comprises at least one of 4. H₂O, CH₃OH, CF₃OH, CF₃CH₂OH, CF₃CF₂OH, (CF₃)₂CHOH, CH₄, C₂H₄, C₂F₆, CHF₃ CCIF₃, C₂H₆, SF₆, Propylene, Propane, NH₃, Pentane, ⁱPrOH, MeOH, EtOH, ⁱBuOH, Benzene, Pyridine.
- A method as claimed in any one of claims 1 to 4, wherein the substrate comprises a 5. metallic substance.
- A method as claimed in claim 5, wherein the metallic substance comprises at least one 6. of gold, silver, copper, iron, mercury, palladium, gallium arsenide, ferrous oxide, indium tin oxide.

١.,


7. A method as claimed in claim 6, wherein the substance comprises a semi-fluorinated sulphur containing compound of the formula:

Where X comprises R-SH, RS-SR or R-S-R, where R denotes the rest of the molecule;

Y comprises a functional group; and

m and n denote respectively the number of fluorinated and non-fluorinated carbon atoms.

- 8. A method as claimed in claim 7, wherein X comprises a disulphide of sulphur.
- 9. A method as claimed in claim 7 or 8, wherein X comprises a thiol.
- 10. A method as claimed in any one of claims 7 to 9, wherein Y comprises a CF₃ functional group.
- 11. A method as claimed in any one of claims 7 to 10, wherein m and n lie within the range of 1 to 20.
- 12. A method as claimed in claim 11, wherein m and n lie within the range of 5 to 10.
- 13. A method as claimed in claim 12, where m is 8 and n is 10.



- 15. A method as claimed in claim 14, wherein the spacer group comprises at least one of CH₂ or CF₂.
- 16. A method as claimed in any one of claims 1 to 5, wherein the substrate comprises at least one of glass, mica, SiO₂, Al₂O₃, or Ga₂O₃.
- 17. A method as claimed in claim 16, wherein the substance comprises a semi-fluorinated silane derivative of the formula:

where Y comprises a functional group; and

m and n denote respectively the number of fluorinated and non-fluorinated carbon atoms.

- 18. A method as claimed in 17, wherein Si comprises a trialkoxy derivative.
- 19. A method as claimed in claim 18, wherein Si comprises at least one of SiCl₃, Si(OCH₃)₃, Si(OCH₂CH₃)₃, Si(OCH₃)₂Cl or Si(CH₂CH₃)₂Cl.

٠:1



20. A method as claimed in any one of claims 17 to 19, wherein Y comprises a CF₃ functional group.

13

- 21. A method as claimed in any one of claims 17 to 19, wherein m and n lie within the range of 1 to 20.
- 22. A method as claimed in claim 21, wherein m and n lie within the range of 5 to 10.
- 23. A method as claimed in claim 22, wherein m is 6 and n is 1.
- 24. A method as claimed in any one of claims 17 to 23, wherein Y further comprises at least one of vinyl, styryl, acryloyl, methacryloyl or alkyne in combination with a spacer group.
- 25. A method as claimed in claim 24, wherein the spacer group comprises at least one of CH₂ or CF₂.
- 26. A method as claimed in any one of the preceding claims, wherein the self-assembled monolayer has an ellipsometry thickness of about 30Å and a water contact angle of about 110°.
- 27. An inkjet head comprising a self-assembled monolayer as claimed in any one of claims 1 to 15 or claim 26, when appendant to any one of claims 1 to 15.
- 28. An electronic, optical or optoelectronic device comprising a self-assembled monolayer as claimed in any one of claims 1 to 5 or claims 16 to 26 or claim 26 when appendant to any one of claims 1 to 5, or 16 to 25.
- 29. A device as claimed in claim 28 comprising a thin film transistor or an organic semiconductor device, or a light emitting diode.

30. A device as claimed in claim 29, wherein the light emitting diode comprises an organic polymer light emitting diode.